



ESD Basic Trolley 500 x 700
RT-TB/ESD/50/70/W-2



ESD Basic Trolley 1000 x 700
RT-TB/ESD/100/70/W-2



ESD Basic Trolley 1500 x 700
RT-TB/ESD/50/150/W-2

ESD Basic Trolley

Feature	ESD BASIC TROLLEY RT-TB/ESD/50/70/W-2	ESD BASIC TROLLEY RT-TB/ESD/100/70/W-2	ESD BASIC TROLLEY RT-TB/ESD/150/70/W-2
Height adjustment type	Manual	Manual	Manual
Height adjustment (1 shelf)	610 – 960 mm	610 – 960 mm	610 – 960 mm
Adjustment method	Stepless (continuous)	Stepless (continuous)	Stepless (continuous)
Width	500 mm	1000 mm	1500 mm
Depth	700 mm	700 mm	700 mm
Number of shelves	2	2	2
Max load – 1 shelf	30 kg	40 kg	50 kg
Max total load	100 kg	100 kg	100 kg
Profile dimensions	30×30×1.5 mm	35×35×1.5 mm	35×35×1.5 mm
Frame sheet thickness	2.5 mm	2.5 mm	2.5 mm
Shelf thickness	25 mm	25 mm	25 mm
Material	Structural steel + double-sided antistatic dissipative with graphite additive, melamine-coated	Same	Same
Color	RAL 7035 (Light Grey) / RAL 9005 (Black)	Same	Same
Castors	ESD Ø100 mm	ESD Ø100 mm	ESD Ø100 mm
ESD protection	Yes	Yes	Yes
Grounding resistance	10 ⁴ – 10 ⁸ Ω	10 ⁴ – 10 ⁸ Ω	10 ⁴ – 10 ⁸ Ω
Optional accessories	Yes	Yes	Yes
Compliance with standards	ANSI/ESD S20.20:2014, PN-EN 61340-5-1:2024, PN-EN ISO 9001:2015, PN-EN ISO 3834-2:2021, PN-EN 1090-1:2009+A1:2011	Same	Same



RT-HTB/ESD/45



RT-HTB/ESD/60