



ESD Technical Trolley 900 X 625



RT-TT/ESD/90/62/T-2



RT-TT/ESD/90/62/T-3



RT-HTT/ESD/45

Specification	RT-TT/ESD/90/62/T-2	RT-TT/ESD/90/62/T-3
Model	ESD TECHNICAL TROLLEY RT-TT/ESD/90/62/T-2	ESD TECHNICAL TROLLEY RT-TT/ESD/90/62/T-3
Height adjustment – 1 shelf	645–945 mm	645–945 mm
Width	900 mm	900 mm
Depth	625 mm	625 mm
Number of shelves	2	3
Load capacity – 1 shelf	50 kg	50 kg
Load capacity – total	30 kg	33 kg
Profil dimension	50 × 30 × 1,5 mm	50 × 30 × 1,5 mm
Sheet thickness – shelf	1,50 mm	1,50 mm
Sheet thickness – construction	2,00 mm	2,00 mm
Internal shelf dimensions	610 × 810 mm	610 × 810 mm
Type of castors	ESD Ø100 mm	ESD Ø100 mm
Color – construction	RAL 7035 (LIGHT GREY)	RAL 7035 (LIGHT GREY)
Color – shelves	RAL 9005 (BLACK)	RAL 9005 (BLACK)
Material	CONSTRUCTION STEEL	CONSTRUCTION STEEL
Resistance grounding	10 ⁴ – 10 ⁸ Ohm	10 ⁴ – 10 ⁸ Ohm
ESD	YES	YES
Compliance with standards	ANSI/ESD S.20.20.2014 PN-EN 61340-5-1:2024 PN-EN ISO 9001:2015 PN-EN ISO 3834-2:2021 PN-EN 1090-1:2009+A1:20	ANSI/ESD S.20.20.2014 PN-EN 61340-5-1:2024 PN-EN ISO 9001:2015 PN-EN ISO 3834-2:2021 PN-EN 1090-1:2009+A1:20