

DataView[®] Software platform for data processing



QUALI STAR+ Energy analysers

- C.A 6116N & C.A 6117 electrical installation testers
- PEL100 power and energy loggers
- C.A 6543, C.A 6547 & C.A 6549 megohmmeters
- C.A 8230 & C.A 8220 power analysers
- C.A 6470N, C.A 6471 & C.A 6472 earth and resistivity testers
- F407 & F607 power and harmonics clamps
- C.A 6240, C.A 6250 & C.A 6292 micro-ohmmeters
- C.A 6417 earth clamp
- Simple Logger II models & Data Logger L452
- DTR 8510 ratiometer
- C.A 6526, C.A 6532 and C.A 6534 insulation testers
- C.A 1821, C.A 1822, C.A 1823 thermometers
- C.A 1110 Lightmeter, C.A 1227 thermo-anemometer, C.A 1246 thermo-hygrometer

Measure up



DataView[®]

Software platform for data processing



DL Transfer

- > C.A 1821, C.A 1822, C.A 1823 thermometers, C.A 1110 Lightmeter, C.A 1227 thermo-anemometer, C.A 1246 thermo-hygrometer
- > L562, CL601, L101, L102, L111, ML912, L261, L481, ML914, AL834, L642, L452 loggers
- > Automatic measurement reports in Word format (.docx)



DataView[®]

- ✓ Configuration of instruments connected to a PC or via Bluetooth
- ✓ Recovery of the measurement data stored in the instrument
- ✓ Backup of measurement files
- ✓ Opening of backup files
- ✓ Processing and creation of reports
- ✓ Export into Excel spreadsheets
- ✓ Export in .pdf format
- ✓ Database management



DTR

- > DTR 8510 ratiometer

MOT

- > C.A 6240
C.A 6250 C.A 6292
micro-ohmmeters



Power Analyser Transfer 2

- > Qualistar+ : C.A 8331, C.A 8333, C.A 8335, C.A 8336, C.A 8435
- Configuration of alarms
- Configuration of transients
- Configuration of trends
- Real-time display



PEL Transfer

- > PEL102, PEL103 & PEL105 power and energy loggers
- Multi-instrument network management
- Real-time display
- Bluetooth and WiFi communication



GTC

> C.A 6417 earth clamp

- Instantaneous acquisition



The measurements taken can also be processed by the multi-product expert processing software

DataView® automatically recognizes the instrument when it is hooked up to the PC and opens the corresponding menu. This menu, shown as a tree structure, gives users direct access to the data recorded in the instrument, its configuration, etc.

DataView® includes numerous predefined report templates for quick report generation in accordance with the applicable standards. Users can create their own templates as required.

Power Analyser Transfer

> Qualistar C.A 8332B and C.A 8334B

- Configuration of alarms
- Configuration of transients
- Configuration of trends
- Real-time display

> F407 and F607 power and harmonics clamps

- Real-time display
- Bluetooth

> C.A 8220 and C.A 8230 power analysers

- Configuration of alarms
- Configuration of transients
- Configuration of trends
- Real-time display



GTT

> C.A 6470N, C.A 6471, C.A 6472 & C.A 6474 earth and resistivity testers

- Remote tests
- Instantaneous acquisition



ICT

> C.A 6116, C.A 6116N and C.A 6117 electrical installation testers

- Customization of measurement campaigns with transfer into the instrument
- Preparation of installation verification reports



MEG


> C.A 6526, C.A 6532, C.A 6534, C.A 6543, C.A 6547, C.A 6549, C.A 6550 and C.A 6555 megohmmeters

- Activation of remote tests
- Real-time display
- DAR, PI and DD ratios
- Graphical plotting of the tests



DataView®

Software platform for data processing



EN 50160 reports for the **QUALISTAR+** models

The EN 50160 standard concerns voltage quality. With increasingly sensitive receivers and a network affected by disturbances due in particular to non-linear loads, it is crucial to check the quality of the voltage supplied.

After proposing automatic configuration of your instrument and the measurement campaign to be run, the software offers comprehensive evaluation functions and drafts automatic reports in compliance with EN50160. The summary page summarizes the results of the campaign. It also includes the location, the conditions, the equipment used and information about the operator.



DataView® is specified for

- Windows** 10
- Vista
- Win 7
- Win 8/8.1.

*You must have Administrator rights on the PC to install DataView®.

**Windows® is a registered trade mark of Microsoft® Corporation

ICT reports in compliance with the applicable standards for installation testers

ICT proposes to define the tree structure which will be used during the actual test campaign (Sites, Parts, Objects) and the tests to be performed for each of the items. Once the campaign has been defined, it can then be recorded in the instrument via the communication link.

This saves significant time in the field. For report generation, in addition to the references of the customer site and the operator, it is possible to predefine the format of the report to be generated by DataView® by choosing in a list of existing templates which comply with the applicable standards: IEC 60364. The report can also be customized.



Connect your instrument to your PC very simply via:

- the RS 232 interface
- the USB link
- Bluetooth
- WiFi

For information and ordering

FRANCE
Chauvin Arnoux
 190, rue Championnet
 75876 PARIS Cedex 18
 Tél : +33 1 44 85 44 85
 Fax : +33 1 46 27 73 89
 info@chauvin-arnoux.fr
 www.chauvin-arnoux.fr

UNITED KINGDOM
Chauvin Arnoux Ltd
 Unit 1 Nelson Ct, Flagship Sq, Shaw Cross
 Business Pk
 Dewsbury, West Yorkshire - WF12 7TH
 Tel: +44 1924 460 494
 Fax: +44 1924 455 328
 info@chauvin-arnoux.co.uk
 www.chauvin-arnoux.com

MIDDLE EAST
CHAUVIN ARNOUX MIDDLE EAST
 P.O. BOX 60-154
 1241 2020 JAL EL DIB - LEBANON
 Tel: +961 1 890 425
 Fax: +961 1 890 424
 camie@chauvin-arnoux.com
 www.chauvin-arnoux.com

