

characteristics ESD Labsit 2 with castors

Article: 9123E fabric

| | | | |
|------------------|-----------|----------------|---------|
| Dimensions in mm | Backrest: | H: | 420 |
| | Seat: | H: | 450-650 |
| | | B: | 450 |
| | | T: | 420 |
| Packing data | Weight | kg | 7,7 |
| | Volume | m ³ | |



Base equipment

Benefit

| | | |
|-------------------|---|--|
| Lab qualification | Washable and disinfectant-proof GMP-compliant and suitable for clean rooms Can be used in labs in safety class S1 to S3. Joint-free and positive-fit elements (hygienic design). | Suitable for labs and all types of areas where hygiene is critical, as well as use in the healthcare sector, universities, biotechnology, chemistry and pharmaceuticals. |
| Conductivity | Conductive comfort pad typical leakage resistance of 10 up 6 Ohm. Volume-conducting castors. | Compliant with the ESD properties acc. to DIN EN 61340-5-1. |
| Handling | Practical handle on backrest. Extremely lightweight. Compact dimensions. | Ensures maximum mobility and simple handling. |
| Ergonomics | Only a single lever has to be operated for adaptation to the user and workplace situation. | Intuitive handling. Labsit can be automatically adapted with its flex functions. Complicated adjustment tasks are dispensed with. |
| Backrest | Plastic backrest with 3D flex function. | The backrest is adapted to the movements of the user and gives way when reclining and during lateral rotation of the upper body. Thus ensuring dynamic sitting and optimal body support in every sitting posture. Intuitive and automatic. |
| Seating surface | Flex function in front edge of seat. | The front edge of the seat is automatically readjusted for leaning forward. As a result, pressure loading is prevented and blood circulation is improved. |
| Seat shell | Black. | Distinctive appeal. Increase in job quality and employee satisfaction. |
| Seat pad | ESD fabric upholstery Duotec: Hard-wearing, breathable and comfortable fabric cover. Fire protection acc. to EN 1021 Part 1, black colour. | The pad is breathable and can absorb and release moisture. Maximum seating comfort is guaranteed thanks to the particularly soft surface. |
| Seat height | Seat height setting, infinitely variable from 450 - 650 mm. | Large seat height adjustment range. |
| Base | Aluminium base. | Very high stability, durable and stable. Elegant and high-quality. |
| Castors/Glides | Load-dependent braked, soft double castors for hard floors. | Chair does not roll away when unloaded, thus minimised risk of accident. |

characteristics ESD Labsit 2 with castors

Article: 9123E fabric

| | | | |
|------------------|-----------|----------------|---------|
| Dimensions in mm | Backrest: | H: | 420 |
| | Seat: | H: | 450-650 |
| | | B: | 450 |
| | | T: | 420 |
| Packing data | Weight | kg | 7,7 |
| | Volume | m ³ | |



Standards

DIN EN 61340-5-1 DIN EN ISO 14644-1 Air purity class 3 GMP-compliant Lab safety class S1 to S3 Tested for harmful substances DIN 68 877-1 GS certificate for "tested safety" Blue Angel Sanitized Quality management DIN EN ISO 9001 Environmental management DIN EN ISO 14001 Tested environmental management EMAS Industrial safety management OHSAS 18001 EcoVadis CSR Rating 2016 Gold.

Verified by certificates from independent testing institutes. Procurement security.

Guarantee

10-year long-term guarantee, of which 3-year full warranty

Assured quality and high efficiency

characteristics ESD Labsit 2 with castors

Article: 9123E fabric

| | | | |
|------------------|-----------|----------------|---------|
| Dimensions in mm | Backrest: | H: | 420 |
| | Seat: | H: | 450-650 |
| | | B: | 450 |
| | | T: | 420 |
| Packing data | Weight | kg | 7,7 |
| | Volume | m ³ | |



| Options | | Benefit |
|---------------------|---|--|
| Accessories/Labclip | For simple and individual marking. Can be easily attached and removed at any time | Customizable and can therefore be clearly assigned to an occupier or area. |
| Armrests | Fixed armrests | Made from plastic |