



1. ELECTRICAL SPECIFICATIONS

Accuracy is calculated as \pm [% readings + (number of dgt * resolution)] at reference conditions

Step/Contact voltage measurements (unit HT2055M)

Measure voltage range	Resolution	Accuracy
0.01 ÷ 19.99mV	0.01mV	$\pm(2.0\% \text{ rdg} + 2\text{dgt})$
20.0 ÷ 199.9mV	0.1mV	
200 ÷ 1999mV	1mV	
2.00 ÷ 19.99V	0.01V	
20.0 ÷ 59.9V	0.1V	

Calculated voltage range	Resolution	Accuracy
0.0 ÷ 199.9V	0.1V	Calculated value (*)
200 ÷ 999V	1V	
1.00kV ÷ 9.99kV	10V	

(*) The calculated value of step/contact voltage is obtained by the relationship: $U_s = U_{meas} \cdot I_{ft} / I_{gen}$; $U_c = U_{meas} \cdot I_{ft} / I_{gen}$
 Range of fault current (selectable): 1A ÷ 200kA
 Input resistance(selectable): 1k Ω , 1M Ω
 Noise reducing/erasing: DSP filtering 55Hz, 64dB rejection on noise at 50/60Hz

Earth resistance measurement (unit HT2055S)

Measurement range	Resolution	Accuracy
0.001 Ω ÷ 1.999 Ω	0.001 Ω	$\pm(2.0\% \text{ rdg} + 5 \text{ dgt})$
2.00 Ω ÷ 19.99 Ω	0.01 Ω	
20.0 Ω ÷ 99.9 Ω	0.1 Ω	
100.0 Ω ÷ 199.9 Ω		$\pm(5.0\% \text{ rdg})$

Open voltage: < 50V AC
 Test current: < 7.5A
 Frequency of test signal: 55Hz
 Influence of probe resistance: $\leq \pm(10\% \text{ rdg} + 10 \text{ dgt})$
 (Rc, Rp)max (10 Ω + 100R) o 2k Ω considering the lower value
 Automatic test on the probe resistance: Yes
 Automatic detection of voltage noise: Yes

Generated current range	Resolution	Accuracy
0.00 ÷ 9.99A	0.01A	$\pm(3.0\% \text{ rdg} + 5 \text{ dgt})$
10.0 ÷ 99.9A	0.1A	$\pm(3.0\% \text{ rdg} + 3 \text{ dgt})$

Generated current: 55A max
 Test voltage: <55V
 Test frequency: 55Hz

Soli resistivity measurement (unit HT2055S)

Measurement range	Resolution	Accuracy
0.00 Ωm ÷ 9.99 Ωm	0.01 Ωm	Calculated value, consider accuracy of Resistance to earth function
10.0 Ωm ÷ 99.9 Ωm	0.1 Ωm	
100 Ωm ÷ 999 Ωm	1 Ωm	
1.00k Ωm ÷ 9.99k Ωm	0.01k Ωm	
10.0k Ωm ÷ 99.9k Ωm	0.1k Ωm	

Measurement principle: Wenner method $\rightarrow \rho = 2 \cdot \pi \cdot \text{distance} \cdot R$



2. GENERAL SPECIFICATIONS

Power unit (HT2055S)

Power supply:	115V/230VAC ($\pm 10\%$), 50/60Hz
Max. power consumption:	750VA
Protection on power supply:	fuse T 5A / 250V (6mm x 30mm)
Safety condition on meter:	IEC/EN61010-1, IEC/EN61557-1
Safety condition on test leads:	IEC/EN61010-031
Installation over 1kVAC:	HD 637 S1
Step/Contact voltage measurement:	EN50522, IEC60936-1
Earth resistance measurements:	IEC/EN61557-5, IEC/EN60364
Spanish guideline:	RAT 2008
Insulation:	class I
Measurement category:	CAT II 300V, CAT IV 50V
Pollution degree:	3
Mechanical protection:	IP30
Display:	LCD dot matrix (128 x 64) with backlight
Internal memory:	1000 locations
Generated current:	values storage for min 24h
Communication interface:	RS-232 (with voltmetric unit)
Dimensions (L x W x H):	563 x 257 x 275mm
Weight (without accessories):	29.5kg

Voltmetric unit (HT2055M)

Power supply:	6x1.2V rechargeable batteries NiMH type AA LR03 6x1.5V alkaline batteries type AA LR03
Battery (chargeable) life:	12 hours (typical)
External power supply:	100-240V AC, 50-60Hz / 12V DC
Safety condition on meter:	IEC/EN61010-1
Safety condition on test leads:	IEC/EN61010-031
Insulation:	double insulation
Measurement category:	CAT IV 50V
Pollution degree:	2
Mechanical protection:	IP40
Display:	LCD dot matrix (128 x 64) with backlight
Auto Power OFF:	after 15 minutes of idleness (not disable)
Internal memory:	1500 locations
Communication interface:	RS-232 and USB (to PC)
Dimensions (LxLaxH):	230 x 115 x 103mm
Weight (with batteries):	1.3kg

ENVIRONMENTAL CONDITIONS:

Reference temperature:	10°C ÷ 30°C
Reference humidity:	35% ÷ 65%RH
Working temperature:	0°C ÷ 40°C
Working humidity:	<80%RH
Storage temperature:	-10°C ÷ 60°C
Storage humidity:	<80%RH

This instrument satisfies the requirements of Low Voltage Directive 2014/35/EU (LVD) and of EMC Directive 2014/30/EU

This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive