



## Cassa portaoggetti dissipativa IDP-STAT®

Contenitori di stoccaggio elettrostaticamente dissipativi in polipropilene.

- Realizzato in polipropilene con un IDP (Polimero Intrinsecamente Dissipativo) con proprietà dissipative permanenti
- Classificazione dei materiali secondo IEC 61340-5-3:
  - Dissipativa superficiale
  - Volume dissipativo
- Impermeabile
- Simbolo di classificazione ESD
- Impilabile
- Dimensione modulare del pallet
- Colore: rosso, giallo
- Stampa: simbolo ESD, simbolo di riciclaggio e n. lotto
- Riciclabile
- Resistenza superficiale:  $R_s = 10^9 - 10^{10}$  Ohm

Modello	Misura
<b>CASSE GIALLE</b>	
5311.05.gelb	300 x 200 x 120 m
5311.10.gelb	400 x 300 x 120 m
5311.14.gelb	400 x 300 x 170 m
5311.20.gelb	400 x 300 x 220 m
5311.31.gelb	400 x 300 x 320 m
5311.24.gelb	600 x 400 x 120 m
5311.34.gelb	600 x 400 x 170 m
5311.42.gelb	600 x 400 x 220 m
<b>COPERCHI GIALLI</b>	
5311.43.gelb	400 x 300 m
5311.64.gelb	600 x 400 m
<b>CASSE ROSSE</b>	
5311.05.rot	300 x 200 x 120 m
5311.10.rot	400 x 300 x 120 m
5311.14.rot	400 x 300 x 170 m
5311.20.rot	400 x 300 x 220 m
5311.31.rot	400 x 300 x 320 m
5311.24.rot	600 x 400 x 120 m
5311.34.rot	600 x 400 x 170 m
5311.42.rot	600 x 400 x 220 m
<b>COPERCHI ROSSI</b>	
5311.43.rot	400 x 300 m
5311.64.rot	600 x 400 m

### Properties:

Basic material	Polypropylene	
Dissipative additive	IDP - Inherently Dissipative Polymer	
	Typical values	Standard
Thermal properties		
Deflection temperature (at 0,45 N/mm <sup>2</sup> load)	90 °C	ASTM D-648
Max. service temperature	80 °C	-

### Product qualification according to IEC 61340-5-3:

	Test method	Limits	Typical values
Surface resistance $R_s$	IEC 61340-2-3	$1 \times 10^4 \leq R_s < 1 \times 10^{11} \Omega$	$10^9 - 10^{10} \Omega$
Volume resistance $R_v$	IEC 61340-2-3	$1 \times 10^4 \leq R_v < 1 \times 10^{11} \Omega$	$10^9 - 10^{10} \Omega$
Point-to-point resistance $R_{p-p}$	IEC 61340-2-3	$1 \times 10^4 \leq R_{p-p} < 1 \times 10^{11} \Omega$	$10^9 - 10^{10} \Omega$
<i>Environmental conditions: 12 ± 3% RH and 23 ± 2°C (conditioning &gt; 48 hours)</i>			

## Accessori disponibili su richiesta

